Standards
SPS EDF N°42

CC-16.-K

Unipolar voltage detector for elbow connectors with capacitive divider 10-30 kV



Description :

Application:

- Unipolar voltage detector for elbow connectors with capacitive divider.
- Maximum operating voltage: 30 kV network.

Features:

- Voltage range : 10 to 30 kV.
- The shape of the contact electrode removes the cap from the separable connector.
- Signalisation :
  - 1 red LED (voltage presence);
  - 1 green LED (stanby state);
  - Timed audio signal.
- Function check by pressing the TEST button:
  - Switch on by flashing red LED
  - Triggering of the clocked sound signal
- Fixing on insulating stick by universal notched tip type "K".

Composition:

- Supplied in a hard case.
- 9 V Lithium Battery.
- NFC TAG.

Optional accessories:

- Insulating stick: CC-45-K
- Stick bag: CM-1-10







Ref.	Battery	Fitting	Use EN	Dimensions [mm]	Height [mm]	Width [mm]	Depth [mm]	Weight [kg]	Frequency	Voltage Range	Operating Voltage AC	Operating Temperature
CC-163-K	4 piles - LR9	K	Indoor	130 x 180 x 40	130	180	80	0,820	50 / 60 Hz	10 - 30 kV	10 - 30 kV	'-15°C/+40°C

CATU S.A.S - 10, Avenue Jean-Jaurès - B.P.2 - 92222
Téléphone : (33) 01 42 31 46 00
Téléphone commercial : (33) 01 42 31 46 46